



# ALL SURFACE COATING(AUST) PTY.LTD.

Unit 37 & 38 No.1 Commercial Road, Highett 3190

Phone 03 95321261 Fax 03 95535226 E-Mail: [ascaust@bigpond.com](mailto:ascaust@bigpond.com)

Registered Office: 9 St.Gwinear Crt, Rawson 3825 Post Office Box 18 Rawson 3825

ABN 66 088 400 659 ACN 088 400 659

Supply and or application of curing compinds, Waterproofing, coloured concrete sealers, epoxy floors Anti graffiti coating.

A S C

## EVENCURE AC

### INTRODUCTION

Evencure AC is an acrylic modified emulsion used as a curing membrane on freshly poured concrete. Evencure AC meets AS3799 requirements and exhibits excellent durability as a concrete sealer.

### BENEFITS

- Dries to a clear finish
- Complies with Australian Standard AS3799
- Achieves water retention of 90% or greater
- Totally waterbased
- Single pack
- Reduces plastic shrinkage
- Environmentally friendly
- Can be applied by spray, roller or brush
- Will not yellow in sunlight
- Eliminates the need for curing by ponded water, damp hessian or polythene sheeting
- Seals concrete surfaces
- Takes most after trades
- Equipment washable in water

### SURFACE APPLICATION

Apply Evencure AC to the concrete as soon as the bleed water has gone and the concrete has hardened sufficiently so as not to be marked by the application process. Apply Evencure AC undiluted at a rate of 1 litre per 5m<sup>2</sup>. Best applied by spray, however, may also be applied by brush, roller or broom.

If aftertrades need to be applied it is recommended that a period of 28 days from the date of pouring has elapsed before any aftertrades are applied.

NOTE: Ensure all equipment is thoroughly cleaned in water.

### TYPICAL PROPERTIES AND APPLICATION DATA

<i>Appearance:</i>	Milky white emulsion
<i>Coverage:</i>	5m <sup>2</sup> per litre
<i>Viscosity:</i>	20 - 22 seconds (Ford #4)
<i>Solids:</i>	40% +/- 1%
<i>Solubility in Water:</i>	Totally soluble
<i>Flash Point:</i>	Not applicable
<i>Solvents:</i>	Not applicable
<i>Shelf Life:</i>	12 months maximum
<i>Dry Time:</i>	<i>Tack Free:</i> 1 - 3 hours
	<i>Hard Dry:</i> 4 - 8 hours
	<i>Trafficable:</i> 24 hours
<i>Application Temperature:</i>	10°C - 35°C
<i>Application By:</i>	- Spray - Brush - Roller - Broom
<i>Packaging:</i>	- 205 Lt drum - 20 Lt container
<i>UN Number:</i>	Not applicable
<i>Hazchem Code:</i>	Not applicable
<i>Packaging Group:</i>	Not applicable
<i>Poison Schedule:</i>	Not applicable
<i>Dangerous Goods Class:</i>	Not applicable

Refer to Material Safety Data Sheet for precautions and personal protection

Disclaimer: Any advice, recommendation, information, assistance or service provided by EVENRANGE Australia in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by EVENRANGE Australia to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by EVENRANGE Australia is provided without liability or responsibility.