



## ALL SURFACE COATING(AUST) PTY.LTD.

Unit 37 & 38 No.1 Commercial Road, Highett 3190

Phone 03 95321261 Fax 03 95535226 E-Mail: [ascaust@bigpond.com](mailto:ascaust@bigpond.com)

Registered Office: 9 St.Gwinear Crt, Rawson 3825 Post Office Box 18 Rawson 3825

ABN 66 088 400 659 ACN 088 400 659

Supply and or application of curing compunds, Waterproofing, coloured concrete sealers, epoxy floors Anti graffiti coating.

A S C

## EVENCURE W30

### INTRODUCTION

Evencure W30 is a wax-based, sprayable curing compound formulated to cure freshly laid concrete. It is a low to medium viscosity, white pigmented emulsion of specially blended waxes.

Evencure W30 meets the requirements of AS3799 for moisture retention in liquid membrane curing compounds.

### USES

Evencure W30 is suitable for curing all freshly laid concrete either smooth or textured, indoors or outdoors.

**NOTE:** After thirty to thirty five (30-35) days the continuous film formed on the concrete surface will begin to degrade due to exposure to UV light. The rate of degradation will depend on the initial film thickness and the degree of UV exposure. Evencure W30 can be used as a debonding agent when applied to the concrete sub-base prior to pouring the concrete base. This allows the two layers to expand and contract differentially without producing cracking.

### CAUTION

If materials are to be bonded to a surface to which Evencure W30 has been applied, sandblasting or solvent treatment is recommended before bonding is attempted.

### SURFACE APPLICATION

Evencure W30 can be easily sprayed with most commonly used spraying equipment including bitumen emulsion sprayers. (Requires a minimum pressure of 280kPa [40 psi]).

Apply Evencure W30 to the concrete as soon as the bleed water has gone and the concrete has hardened sufficiently so as not to be marked by

the application process. Apply Evencure W30 undiluted at a rate of 1 litre per 5m<sup>2</sup>. Best applied by spray, however, may also be applied by brush, roller or broom.

Evencure W30 performs best when one complete coat is applied, until a continuous uniform film is achieved.

### TYPICAL PROPERTIES AND APPLICATION DATA

<i>Appearance:</i>	Low viscosity, homogenous white liquid
<i>Coverage:</i>	5m <sup>2</sup> per litre
<i>Viscosity:</i>	0.05 - 0.30 Pascal seconds
<i>Solids:</i>	32% +/- 1%
<i>Solubility in Water:</i>	Negligible
<i>Flash Point:</i>	Not applicable
<i>Solvents:</i>	Not applicable
<i>Shelf Life:</i>	3 months maximum
<i>Dry Time:</i>	<i>Tack Free:</i> Not applicable <i>Hard Dry:</i> Not applicable
<i>Application Temperature:</i>	10°C - 35°C
<i>Application By:</i>	- Spray - Brush - Roller - Broom
<i>Packaging:</i>	- 205 Lt drum - 20 Lt container
<i>UN Number:</i>	Not applicable
<i>Hazchem Code:</i>	Not applicable
<i>Packaging Group:</i>	Not applicable
<i>Poison Schedule:</i>	Not applicable
<i>Dangerous Goods Class:</i>	Not applicable

**Refer to Material Safety Data Sheet for precautions and personal protection**

**Disclaimer:** Any advice, recommendation, information, assistance or service provided by EVENRANGE Australia in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by EVENRANGE Australia to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by EVENRANGE Australia is provided without liability or responsibility.