

MATERIAL SAFETY DATA SHEET
CURE XD40

COMPANY DETAILS
of 2

Page 1

Name: All Surface Coating (Aust)Pty.Ltd.
Address: Unit 37 & 38 No 1 Commercial Road, HIGHETT, VIC. 3190
Phone: 03 95321261
Fax: 03 95535226
Mob: 0418367454

IDENTIFICATION

Product Name:	CURE XD40	U.N. Number:	N/A
Shipping Name:	Polymer emulsion	Dangerous Goods Class:	N/A
Subsidiary Risk:	N/A	Hazchem Code:	N/A
Poisons Schedule:	N/A	Packaging Group:	N/A

Chemical Description: Acrylic modified emulsion

Use: Concrete curing compound

PHYSICAL DESCRIPTION / PROPERTIES

Appearance:	Milky white emulsion	Flammability Limit(%):	N/A
Odour:	Slight fruity	In organic solvents:	N/A
Solubility in water(g/l):	Totally soluble	Vapour Pressue @25 C	N/A
Boiling Point:	100 C	Relative Density:	0.98
pH:	>8	Shelf Life:	18
mth,max			
Solids (%):	35% +/- 1%	Other properties:	NAS
Flash Point (C):	N/A (Non flammable)		

INGREDIENTS

Chemical Entity	CAS Number	% By Weight	Threshold Limit Value			
			Time Weight Average ppm	Average mg/m	Short Term Exposure ppm	ppm
<u>mg/m</u>						
Mixed Acrylates	80-62-6	Trace	100	410	125	510
Ammonia	7664-41-7	0.27%	25	17	35	24

HEALTH HAZARD INFORMATION

EMERGENCY AND FIRST AID PROCEDURES

Swallowed: No serious poisoning hazard. Drink plenty of water and seek medical assistance.
Eye: Flush with copious volumes of water, lifting lids occasionally. Seek medical attention.
Skin: Thoroughly wash exposed area with soap and water. Remove effected clothing and launder before re-use.
Inhaled: Move subject to fresh air. Apply artificial respiration or oxygen if necessary.

N/A = Not applicable
NAS = Not assigned

MSDS Cure XD40 Ed. 126/09/02

PRECAUTIONS FOR USE

Effects of Overexposure: Inhalation of high vapour concentrations may cause intoxication and/or difficulty in breathing. Prolonged cause irritation and defatting.

Respiratory Protection: Use appropriate ventilation. If product is sprayed, vapour generated, therefore it is recommended to use an appropriate respirator for this operation.

Ventilation: Sufficient ventilation or local exhaust is recommended.

Personal Protection: Gloves Long Impervious, PVC content.
Normal working clothing covering arms and legs.
Wear eye protection and ensure there is eyewash facility available.

SAFE HANDLING INFORMATION

Storage and Transport: Avoid heat, Flames, oxidising agents. Store under cover and away from sunlight and frost.

Spills: Dyke or otherwise contain spillage. Particularly prevent spillage from going to stormwater drains. Pump spillage into empty drums then absorb residues in sand or vermiculite or earth. Then dispose of in accordance with local government regulations.

Disposal: **Observe all Federal, State and Local regulations.** Contaminated absorbent to be deposited in approved disposal facility.

Fire/Explosion Hazard: Explosion Limit - upper : lower N/A
Dust explosion hazard: N/A
Hazardous decomposition products: -Oxi
possibly
Hazardous polymerisation products/reaction: oxi
Extinguishing media: -will
N/A

CONTACT POINTS

ORGANIZATION	LOCATION	TELEPHONE
All Surface Coating(Aust)P/L Hours	Unit 37 & 38 No. 1 Commercial Road, HIGHETT, VIC, 3190	(03) 9498 (03) 9498 0418

All information contained in this Data Sheet is as accurate and up to date as possible. No liability is expressed or implied as to its accuracy, reliability or completeness.