

Safety Data Sheet

Issue Date: 22/12/2016

ISSUED by CEMENTAID [Page: 1 of 7]

Product Name: **ROKITE PR**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

GHS Product Identifier ROKITE PR
Company Name CEMENTAID (VIC) PTY LTD (ABN 18 004 518 889)
Address 15 Clarice Rd, Box Hill South, Victoria 3128 Australia
Telephone/Fax Number
Tel: +61 3 9890 0487
Fax: +61 3 9890 6223
Emergency Telephone 1800 638 556 (24hr)

Recommended use of the chemical and restrictions on use
Sealer for Concrete and Masonry

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Acute Toxicity – Dermal: Category 4

Acute Toxicity – Inhalation: Category 4

Flammable Liquids: Category 3

Skin Corrosion/Irritation: Category 2

STOT Single Exposure: Category 3 (narcotic)

STOT Single Exposure: Category 3 (respiratory tract)

Signal Word (s)

WARNING

Hazard Statement (s)

H226 Flammable liquid and vapour

H312 Harmful in contact with skin

H315 Causes skin irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

Pictogram (s)

Flame, Exclamation mark



Safety Data Sheet continued

Issue Date: 22/12/2016 ISSUED by CEMENTAID [Page: 2 of 7]

Product Name: **ROKITE PR**

Precautionary statement – Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion-proof electrical/ventilating/lighting/equipment
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P261 Avoid breathing dust/fume/gas/mist/vapours/spray
P264 Wash contaminated skin thoroughly after handling
P271 Use only outdoors in a well-ventilated area
P280 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statement – Response

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 Call a POISON CENTRE (eg Australia Phone 131 126) or doctor/physician if you feel unwell
P332+P313 If skin irritation occurs: Get medical advice/attention
P362 Take off contaminated clothing and wash before reuse
P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam for extinction

Precautionary statement – Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed
P403+P235 Store in a well-ventilated place. Keep cool
P405 Store locked up

Precautionary statement – Disposal

P501 Dispose of contents/container to an approved wasted disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

| Name | CAS | Proportion |
|--|-----------|------------|
| Xylene | 1330-20-7 | 50-70% |
| Butyl Acetate | 123-86-4 | <10% |
| Ethyl Acetate | 141-78-6 | <10% |
| Ingredients determined not to be hazardous | | Balance |

4. FIRST AID MEASURES

Inhalation If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin Remove contaminated clothing. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye Contact If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities Eye wash, safety shower and normal washroom facilities.

Advice to Doctor Treat symptomatically.

Other Information For advice in an emergency, contact a Poisons Information Centre (Phone eg Australia 131 126) or doctor at once.

Safety Data Sheet continued

Issue Date: 22/12/2016 ISSUED by CEMENTAID [Page: 3 of 7]

Product Name: **ROKITE PR**

5. FIRE FIGHTING MEASURES

| | |
|---|--|
| Suitable Extinguishing Media | Use carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used |
| Unsuitable Extinguishing Media | Do not use water jet. |
| Hazards from Combustion Products | Under fire conditions this product may emit toxic and/or irritating fumes smoke and gases including carbon monoxide carbon dioxide and oxides of nitrogen. |
| Specific Hazards Arising from the Chemical | Flammable liquid. Keep storage tanks, pipelines, fire-exposed surfaces etc cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create a fire hazard. Heating can cause expansion or decomposition leading to violent rupture of containers. |
| Hazchem Code | •3Y |
| Precautions in connection with Fire | Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Use water spray to cool storage containers and tanks, pipelines and fire exposed surfaces. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|-----------------------------|--|
| Emergency Procedures | Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert, absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs, inform the local water and waste management authorities in accordance with local regulations. |
|-----------------------------|--|

7. HANDLING AND STORAGE

| | |
|--------------------------------------|---|
| Precautions for Safe Handling | Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with adequate ventilation. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers closed when not in use. Take precautionary measures against static discharges. Keep material away from sparks, flames and other ignition sources. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities. |
| Conditions for Safe Storage | Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, incompatibles, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| | |
|---|---|
| Occupational Exposure Limit Values | No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below: |
|---|---|

| | | |
|----------------------|---------------------------------|----------------------------------|
| | TWA: | STEL: |
| Xylene | 80 ppm, 350 mg/ m ³ | 150 ppm, 655 mg/ m ³ |
| Ethyl Acetate | 200 ppm, 720 mg/ m ³ | 400 ppm, 1440 mg/ m ³ |
| Butyl Acetate | 150 ppm, 713 mg/m ³ | 200 ppm, 950 mg/ m ³ |

| | |
|-------------|--|
| TWA | Time Weighted Average: The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week. |
| STEL | Short Term Exposure Limit: The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday. |

Safety Data Sheet continued

Issue Date: 22/12/2016 ISSUED by CEMENTAID [Page: 4 of 7]

Product Name: **ROKITE PR**

Biological Limit Values

Name: Xylene
Determinant: Methylhippuric acids
Specimen: Creatinine in urine
Value: 1.5g/g
Sampling time: End of Shift

Source: American Conference of Industrial Hygienists (ACGIH)

Appropriate Engineering Controls

Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres – Classification of areas _ Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

| Properties | Description | Properties | Description |
|-------------------------|---|------------------------------|---|
| Appearance | Colourless liquid (May be coloured with inert pigments) | Colour | Colourless (May be coloured using inert pigments) |
| Odour | Not available | Melting Point | Not applicable |
| Boiling Point | 138-144° C | Solubility in Water | Not available |
| Specific Gravity | 0.9 | pH | Not available |
| Vapour Pressure | 7.99 mmHg (25C) (Xylene) | Vapour Density (Air=1) | Not available |
| Evaporation Rate | Not available | Coefficient Water/Oil Distr. | Not available |
| Odour Threshold | Not available | Viscosity | Not available |
| Volatile Component | 75%v/v | Flash Point | 24° C (Closed Cup) |
| Flammability | Flammable liquid | Auto-Ignition Temperature | Not available |
| Flammable Limits -Lower | 0.6%v/v | Flammable Limits - Upper | 7%v/v |
| Explosion Properties | Not available | Oxidising Properties | Not available |

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of storage and handling

Reactivity and Stability

Reacts with incompatible materials

Conditions to Avoid

Heat, open flames and other sources of ignition

Incompatible Materials

Strong oxidising agents

Hazardous Decomposition Products

Thermal decomposition may result in release of toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen

Possibility of hazardous reactions

Reacts with incompatible materials

Hazardous Polymerization

Will not occur

Safety Data Sheet continued

Issue Date: 22/12/2016

ISSUED by CEMENTAID [Page: 5 of 7]

Product Name: **ROKITE PR**

11. TOXOLOGICAL INFORMATION

| | |
|---|--|
| Toxicology Information | No toxicity data available for this material |
| Acute Toxicity – Oral | For Xylene – LD50 (rat): 4,300 mg/kg |
| Acute Toxicity – Inhalation | For Xylene – LC50 (rat): 5,000 ppm/4h |
| Acute Toxicity – Dermal | For Xylene – LD50 (rabbit) : >1,700 mg/kg |
| Ingestion | May irritate the gastric tract causing nausea and vomiting |
| Inhalation | Harmful if inhaled. May cause respiratory irritation. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system. May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting. |
| Skin | Harmful in contact with skin. Product can be absorbed through skin with resultant harmful systemic effects. Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis |
| Eye | May cause irritation to eyes. Symptoms may include redness, tearing, stinging and swelling |
| Respiratory sensitisation | Not expected to be a respiratory sensitiser |
| Skin Sensitisation | Not expected to be a skin sensitiser |
| Germ cell mutagenicity | Not considered to be a mutagenic hazard |
| Carcinogenicity | Not considered to be a carcinogenic hazard |
| Xylene is listed as a Group3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC). | |
| Reproductive Toxicity | Not considered to be toxic to reproduction |
| STOT-single exposure | May cause respiratory irritation. May cause drowsiness or dizziness |
| STOT-repeated exposure | Not expected to cause toxicity to a specific target organ |
| Aspiration Hazard | Not expected to be an aspiration hazard |
| Chronic Effects | Prolonged or repeated skin contact may cause defatting leading to dermatitis. Prolonged or repeated exposure may also damage liver, kidneys and central nervous system. Can cause headache, excitement, dizziness, drowsiness and nausea |

12. ECOLOGICAL INFORMATION

| | |
|--|---|
| Ecotoxicity | No ecological data available for this material |
| Persistence & Degradability | Not available |
| Mobility | Not available |
| Bioaccumulative Potential | Not available |
| Other Adverse Effects | Not available |
| Environ. Protection | Do not allow product to enter drains, waterways or sewers |

13. DISPOSAL CONSIDERATIONS

| | |
|--------------------------------|---|
| Disposal considerations | Disposal of spilled or waste material must be carried out in accordance with the relevant local and national government regulations. Advise flammable nature. Empty containers may contain flammable residues. Do not puncture, cut or weld empty containers. |
|--------------------------------|---|

Safety Data Sheet continued

Issue Date: 22/12/2016 ISSUED by CEMENTAID [Page: 6 of 7]

Product Name: **ROKITE PR**

14. TRANSPORT INFORMATION

Transport Information

This material is classified as a Dangerous Goods Class 3 -Flammable Liquid according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 Flammable Liquids are incompatible in a placard load with any of the following:

- Class 1, Explosives
- Division 2.1, Flammable Gases (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500L)
- Division 2.3, Toxic Gases
- Division 4.2, Spontaneously Combustible Substances
- Division 5.1, Oxidising substances and Division 5.2 Organic Peroxides
- Class 6, Toxic and Infectious Substances (where the flammable liquid is nitromethane)
- Class 7, Radioactive Substances

Marine Transport (IMO/IMDG)

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea

| | |
|----------------------|---|
| U.N. Number | 1993 |
| Proper Shipping Name | FLAMMABLE LIQUID, N.O.S. - (CONTAINS: XYLENE) |
| Class | 3 |
| Packing Group | III |
| EMS NO. | F-E, S-E |
| Special Provision | 223,274,955 |

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) a Dangerous Goods Regulations for transport by air.

| | |
|--|---|
| U.N. Number | 1993 |
| Proper Shipping Name | FLAMMABLE LIQUID, N.O.S. - (CONTAINS: XYLENE) |
| Class | 3 |
| Packing Group | III |
| Packaging Instructions (passenger & Cargo) | 355 |
| Packaging Instructions (cargo only) | 366 |
| Hazard Label | Flammable Liquid |
| Special Provision | A3 |

U.N. Number 1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. - (CONTAINS: XYLENE)

Transport hazard class(es) 3

Packaging Group 111

Hazchem Code •3Y

Special Precautions for User Not available

IERG Number 14

IMDG Marine Pollutant No

Transport in Bulk Not available

15. REGULATORY INFORMATION

Regulatory Information

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule S6

Australia (AICS) The listed chemicals are included in Australian Inventory of Chemical Substances (AICS) or otherwise notified under NICNAS

Safety Data Sheet continued

Issue Date: 22/12/2016 ISSUED by CEMENTAID [Page: 7 of 7]

Product Name: **ROKITE PR**

16. OTHER INFORMATION

Date of preparation or last revision of SDS SDS Created: December 2016

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice
Standard for the Uniform Scheduling of Medicines and Poisons
Australian Code for the Transport of Dangerous Goods by Road & Rail
Model Work Health and Safety Regulations, Schedule10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals
Workplace exposure standards for airborne contaminants, Safe Work Australia
American Conference of Industrial Hygienists (ACGIH)
Globally Harmonised System of classification and labelling of chemicals

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF.XML, XFO, and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd. Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd