

EVENRANGE CONCRETE SOLUTIONS

EVENCURE AC—Water based Acrylic Curing Compound

INTRODUCTION

Evencure AC is an acrylic modified emulsion used as a curing membrane on freshly poured concrete. Evencure AC meets AS3799 requirements and exhibits excellent durability as a concrete sealer.

BENEFITS

Dries to a clear finish

Complies with Australian Standard AS3799

Achieves water retention of 90% or greater

Totally water based

Single pack

Reduces plastic shrinkage

Meets low VOC requirements

Can be applied by spray, roller or brush

Will not yellow in sunlight

Eliminates the need for curing by ponded water, damp hessian or polythene sheeting

Seals concrete surfaces

Takes most after trades

Equipment washable in water

USES

Evencure AC is suitable for curing all freshly laid concrete either smooth or textured, indoors or outdoors.

SURFACE APPLICATION

Apply Evencure AC to the concrete as soon as the bleed water has gone and the concrete has hardened sufficiently so as not to be marked by the application process. Apply Evencure AC undiluted at a rate of 1 litre per 5m². Best applied by spray, however, may also be applied by brush, roller or broom. If aftertrades need to be applied it is recommended that a period of 28 days from the date of pouring has elapsed before any aftertrades are applied.

NOTE: Ensure all equipment is thoroughly cleaned in water.

Page 1 of 2

Evenrange Pty. Ltd ABN 92 062 754 545
12 Frankston Gardens Drive, Carrum Downs. Vic 3201
Phone: 039 782 3233 Fax 039 782 3244

EVENRANGE

CONCRETE SOLUTIONS

EVENCURE AC—Water based Acrylic Curing Compound

TYPICAL PROPERTIES AND APPLICATION DATA

| | |
|---------------------------------|--|
| <i>Appearance:</i> | Milky white emulsion |
| <i>Coverage:</i> | 5m ² per litre |
| <i>Viscosity:</i> | 20 - 22 seconds (Ford #4) |
| <i>Solids:</i> | 30 % +/- 1% |
| <i>Solubility in Water:</i> | Totally soluble |
| <i>Flash Point:</i> | Not applicable |
| <i>Solvents:</i> | Not applicable |
| <i>Shelf Life:</i> | 12 months maximum |
| <i>Dry Time:</i> | <i>Tack Free:</i> 30 mins |
| | <i>Hard Dry:</i> 4 hours |
| | <i>Trafficable:</i> 12 hours |
| <i>Application Temperature:</i> | 10°C - 35°C |
| <i>Application By:</i> | - Spray - Brush - Roller - Broom |
| <i>Packaging:</i> | - 1000Lt Palletcons - 205 Lt Epon lined drum - 20 Lt Plastic Container |
| <i>UN Number:</i> | Not applicable |
| <i>Hazchem Code:</i> | Not applicable |
| <i>Packaging Group:</i> | Not applicable |
| <i>Poison Schedule:</i> | N/A |
| <i>Dangerous Goods Class:</i> | Not applicable |

Refer to Material Safety Data Sheet for precautions and personal protection.

Disclaimer: Any advice, recommendation, information, assistance or service provided by application is in good faith and is believed by EVENRANGE PTY LTD to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by EVENRANGE PTY LTD is provided without liability.