



4 Hewitt St, Moorabbin
Ph: 03 9532 1387 Fax: 03 9553 5226
Email: kencrp@bigpond.com
www.concreterepairproducts.com.au

CRP X40

INTRODUCTION

CRP X40 is a blend of resins and surfactants emulsified in water and are specially formulated to cure freshly laid concrete. The impervious film formed by CRP X40 prevents excessive water evaporation, promotes efficient cement hydration, minimises shrinkage whilst increasing durability of the concrete surface.

BENEFITS

- Complies with Australian Standards AS3799
- Achieves water retention of 90% or greater
- Increased abrasion resistance
- Contains no wax
- Eliminates the need for curing by ponded water, damp hessian or polythene sheeting
- Reduces concrete dusting
- Reduces plastic shrinkage
- One coat application
- Can be removed, if required, by ConClena (stripper / degreaser)
- Equipment washable in water
- May have red fugitive dye added

USES

CRP X40 is suitable for curing all freshly laid concrete either smooth or textured, best used outdoors. **If used indoors grinding may be required to remove it where after trades are To be applied**

SPECIAL FEATURES

Due to its unique formulation and blend of resins, CRP X40 will begin to break down after 7 days and, if applied at the specified application rates, will totally oxidise and leave the surface, subject to UV exposure, within 45 - 55 days of the application.



SURFACE APPLICATION

Apply CRP X40 to the concrete as soon as the bleed water has gone and the new concrete has hardened sufficiently so as not to be marked by the application process. Apply CRP X40 undiluted at a rate of 1 litre per 5 m². Best applied by spray, however, may also be applied by brush, roller or broom.

TYPICAL PROPERTIES AND APPLICATION DATA

Appearance: Milky homogenous liquid or with red fugitive dye

Coverage: 5m² per litre

Viscosity: 0.22 Pascal seconds

Solids: 49% +/- 1%

Solubility in Water: Soluble

Flash Point: 84°C

Solvents: Not applicable

Shelf Life: 12 months maximum

Dry Time: Tack Free: 1 - 3 hours

Hard Dry: 4 - 8 hours

Trafficable: 24 hours

Application Temperature: 10°C - 35°C

Application By: - Spray - Brush

- Roller - Broom

Packaging: - 205Lt Eponlined drum

- 20 Lt Plastic Cube

UN Number: Not applicable

Hazchem Code: Not applicable

Packaging Group: Not applicable

Poison Schedule: 5

Dangerous Goods Class: Not applicable

Refer to Material Safety Data Sheet for precautions and personal protection

Disclaimer: Any advice, recommendation, information, assistance or service provided by CRP in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by CRP to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by CRP is provided without liability